



Certificate of Conformity

Certificate: 14059-2G

Master Contract: LC 1076058

Project: 14175

Date Issued: April 10, 2015

Issued to: Fire by Design
3255 Pepper Lane Suite 109
Las Vegas, Nevada 89120
USA

Certification System Type 3
(ISO / IEC Guide 67)

The products listed below are eligible to bear the LabTest Certification Mark with adjacent indicators 'C' and 'US', and the subject area as shown below.



Issued by:

A handwritten signature in blue ink, appearing to read "Kavinder Dhillon".

Certification Manager

PRODUCTS

- **Outdoor Decorative Gas Appliance**
- **Model:** Vulcan Fire Module – VFM
Automated Tiki Torch - ATT
- **Ratings:** ATT & VFM – 21,000 BTU/hr - Natural Gas Supply at 7” water column.
ATT-LP & VFM –LP – 21,000 BTU/hr – Liquid Petroleum Supply at 11” water column.
VFM, VFM-LP, ATT & ATT-LP – 24Vac / 1.5A / 60Hz or optional 12 Vac system.

APPLICABLE REQUIREMENTS & SUBJECT AREA

- ANSI Z21.97: 2014 / CSA 2.41: 2014 – Outdoor Decorative Gas Appliances
- CSA C22.2 No. 3 M1988 (R2014) – Electrical Features for Fuel Burning Equipment

CONDITIONS OF ACCEPTABILITY

- Intended to be used outdoors only with either natural gas or liquid petroleum.
- VFM model to be used with natural gas at 7" water column.
- VFM-LP model to be used with liquid propane at 11" water column.
- Both models are intended to be fixed location once installed according to manufacturer's instructions.
- ATT models are constructed of the VFM with either a gas conduit extension allowing for placement of the tiki torch cone head, or with a decorative sleeve placed over the burner rising vertically for decorative fire feature.
- VFM & ATT models are for use with natural gas only, the "LP" designation after the model number indicates that model is for use with liquid petroleum only.
- ATT & ATT-LP were tested with the CCTH, Copper Cone Tiki Torch Head.
- All 12Vac rated models shall include "-12Vac" added to the model name. Marking labels' electrical ratings shall be reflective of the 12Vac rating for all "-12Vac" models.
- All 12Vac rated models shall include Installation and Operating Instructions applicable to the 12Vac electrical ratings. Such instructions are on file with LabTest Certification, Inc. and meet the standard requirements.

The 'C' and 'US' indicators adjacent to the LabTest Certification Mark shall signify that the product has been evaluated by an accredited laboratory to the applicable CSA and UL Standards respectively. The subject area shall be displayed with the LabTest Certification Mark to identify the Standard Number, and Revision Level.